


ALL IN ONE

ASX4000

cod. ASX-4000



**MUSCOLI COINVOLTI
MUSCLE GROUPS**

■ Full body

OPTIONAL



COD. J-ARMSASX2-4-5
Jammer arms



COD. LAT-SEATASX2-4-5
Lat seat



COD. LEG-PRESSASX
Leg press




COD. W-HOLDERASX
Perno porta pesi
Weight plates holder



COD. M-BARASX
Multifunctional bar



COD. LPDASX2-4-5
Lat pull down



STRENGTH - ALL IN ONE

PULLEY regolabile 264-1839 mm su 22 livelli interasse 75 mm
PACCO PESI in acciaio 2x90kg
J-CUP/SAFETY SPOTTER ARMS Extra strong spessore 5 mm con protezione UHMW (Ultra High Molecular Weight). Regolabile 314-1814 mm su 31 livelli interasse 50 mm
DIMENSIONI PRODOTTO: 1516x1938x2167 mm
PESO MASSIMO UTILIZZATORE 150 Kg
PESO: 369.5 kg
CLASSE D'UTILIZZO PROFESSIONALE (EN20957-1 / EN957-2 / EN957-4 classe S)

PULLEYS adjustable on 22 levels (264-1839 mm) distance 75 mm
WEIGHT STACK steel weight stack 2x90 kg
J-CUP/SAFETY SPOTTER ARMS Extra strong - 5 mm thickness with UHMW (Ultra High Molecular Weight) protection pads, adjustable on 31 levels (314-1814 mm) distance 50 mm
SET UP SIZE 1516x1938x2167 mm
MAX USER WEIGHT 150 Kg
WEIGHT: 369.5 kg
COMMERCIAL USE (EN20957-1 / EN957-2 / EN957-4 class S)

- Struttura tubolare a sezione rettangolare 50x70 mm - spessore 2,5 mm/2 mm e quadrata 50x50 mm - spessore 3 mm
- Ratio: 1:2 / fly handle - 1:2 / lat pull down - 1:2 / seated rowing
- Bilanciere: 1936 mm, scorrimento su cuscinetti a sfera, 2 sicurezze con gancio regolabile, regolabili su 12 posizioni (622 - 1832 mm), passo 110 mm. Diametro porta dischi da 50 mm
- DOTAZIONI/NOTE 3-IN-1 dual pulley, smith machine, rack. 2 J-hook, coppia fermi di sicurezza bilanciere con rulli gambe in foam, barra trazioni, parallele, porta bilanciere, 6 porta dischi ø50 mm, 8 ferma dischi a molla ø49 mm. Attachments: cavigliera, corda, landmine, 2 maniglie trazioni regolabili, barra tricipiti, barra tricipiti dritta, bilanciere e bilanciere CURL.

- Structure section rectangular tubing 50x70 mm - thickness 2,5 mm/2 mm and square tubing 50x50 mm - thickness 3 mm
- Ratio: 1:2 / fly handle - 1:2 / lat pull down - 1:2 / seated rowing
- Barbell: 1936 mm, linear bearings sliding, 2 safety systems with hook to avoid barbell falling, vertically adjustable on 12 levels (622 - 1832 mm), distance 110 mm. Weight plate holder diameter suitable for ø50 mm weight plates
- EQUIPMENT/NOTES 3-IN-1 dual pulley, smith machine, rack. 2 J-hooks, 2 safety spotter arms with 1 set leg holder foam, chin-up bar, dip up bar, barbell storage, 6 weight plates holders for ø50 mm plates, 8 olympic spring clips ø49 mm. Attachments: ankle strap, rope, landmine, 2 adjustable Y- handles, V-bar, short straight bar, straight bar and curved bar.

